

SES SCUTTLE HOLE COVER



- *Reflects 97% of Radiant Heat*
- *Insulates & Air Seals Attic Access*

- *Quick Installation*
- *Easy Zipper Access to Attic*



Meets and Exceeds Code Requirements for All Climate Zones



Don't Let Your Hard Earned Money Slip Through The Cracks!



EASY TO INSTALL WITH A THERMAL VALUE UP TO R-58

Please Refer to Back for R-Value Chart



Reflective Insulation Supplied By:



*See Reverse Side for Installation Instructions
or visit our website at www.southeastenergy.solutions*



MADE IN THE USA
US PATENT PENDING

SES SCUTTLE HOLE COVER

Economical Solution for Immediate Energy Savings!

BENEFITS OF SES SCUTTLE HOLE COVER

- Increase Energy Savings
- Non-toxic
- Excellent vapor barrier
- Installs easily with Crown stapler or hammer
- Superior thermal performance
- Flexible and durable
- Improves insulation system performance
- Great for new construction or retrofits
- Reflects up to 97% of radiant heat
- Simple installation and heavy duty zipper allows for easy attic access.
- Insert insulation batt into pocket and close the Velcro tab
- Excellent air sealing to keep out harmful attic pollutants
- **Insulation insertion and Installation video clips are on the website**



PRODUCT DIMENSIONS & DESCRIPTIONS: Double sided scrimmed aluminum foil laminated to polyethylene foam (1/4" nominal thickness)
CORE MATERIAL: Polyethylene
FACINGS AVAILABLE: Foil/Foil
FLAME AND SMOKE: ASTM E-84
FLAME SPREAD: Less than 25, SMOKE DEVELOPED: Less than 50
FULL SCALE FIRE TEST: NFPA 286 - Foil/Foil Passed
R-VALUE: Up to R-9 with current application*
PERM RATING: E-96 - .008

WARNING: Although Insulation Products are all fire tested to ASTM and/or NFPA standards; it is recommended that they or any insulation material should not be exposed to open flame or other ignition sources of sufficient intensity during shipment, storage or installation.

Southeast Energy Solutions, Inc.
www.southeastenergy.solutions
 Email: info@southeastenergy.solutions



ASTM C518 - Testing
Provided By:
 R & D Services
 P.O.Box 2400
 Cookeville, TN 38502-2400

ASTM E-283 Air Leakage:
 Results (1.44 cfm/ft2)
 Reference 2015 IECC/IRC,
 Section R402.4.5/N1102.4.5

E-283 Testing provided by:
 Intertek Architectural
 Testing
 130 Derry Court
 York, PA 17406

Overall R-Value for the Insulation Assembly with Low-Emittance Surfaces

Insulation	Heat Flow Down (summer)	Heat Flow-Up (winter)
13	22.1 (18.5)	15.6 (14.9)
19	28.1 (24.5)	21.6 (20.9)
21	30.1 (26.5)	23.6 (22.9)
30	39.1 (35.5)	32.6 (31.9)
38	47.1 (43.5)	40.6 (39.9)
49	58.1 (54.5)	51.6 (50.9)

*Numbers in parantheses are for upper surface covered with dust, fibers, or other particulate material. The upper surface can be cleaned.



* Can custom make to any size.
 Full size knee wall attic access door sizes are available